


SHOTCRETE HOSE / GROUT HOSE



Applications	For spraying of cement and abrasive slurry materials such as concrete, gypsum, plaster, grout and mortar. For use in heavy construction sites. Excellent kinking resistance.
Tube	Excellent abrasion resistant synthetic rubber (Referring to DIN 53516)
Reinforcement	High tensile synthetic fabric
Cover	High abrasion and weather resistant synthetic rubber
Marking	INTER SC600 SHOTCRETE HOSE - BP 1800PSI - WP 600PSI




Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1	25	25.4	39.0	40	600	120	1800	BX-41001	BX-61001
1.1/2	38	38.0	54.0	40	600	120	1800	BX-41002	BX-61002
2	51	50.8	68.0	40	600	120	1800	BX-41003	BX-61003
2.1/2	63	63.5	83.0	40	600	120	1800	BX-41004	BX-61004
3	76	76.2	98.0	40	600	120	1800	BX-41005	BX-61005
4	102	101.6	122.0	40	600	120	1800	BX-41006	BX-61006
5	127	127.0	149.0	40	600	120	1800	BX-41007	BX-61007

For sizes other than listed above, please contact us

SANDBLAST HOSE



Applications	For conveying abrasive sandblasting materials in cleaning and blasting metal, casting and concrete surfaces.
Tube	Excellent abrasion resistant synthetic rubber *Abrasion resistance : DIN 53516 ≤ 60mm³
Reinforcement	High tensile synthetic fabric
Cover	High abrasion and weather resistant synthetic rubber
Marking	INTER SB175 SANDBLAST HOSE - HEAVY DUTY - BP 530PSI - WP 175PSI



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1/2	13	13.0	29.0	12	175	36	530	BA-52001	BA-62001
3/4	19	19.0	33.0	12	175	36	530	BA-52002	BA-62002
1	25	25.4	39.0	12	175	36	530	BA-52003	BA-62003
1.1/4	32	32.0	48.0	12	175	36	530	BA-52004	BA-62004
1.1/2	38	38.0	54.0	12	175	36	530	BA-52005	BA-62005
2	51	50.8	69.0	12	175	36	530	BA-52006	BA-62006
2.1/2	63	63.5	82.0	12	175	36	530	BA-52007	BA-62007
3	76	76.2	96.0	12	175	36	530	BA-52008	BA-62008
4	102	101.6	122.0	12	175	36	530	BA-52009	BA-62009

ISO 3861 is available upon request

For sizes other than listed above, please contact us

ISO 3861*

