


OIL SUCTION & DISCHARGE HOSE 150PSI



Applications	For suction and discharge of petroleum products, of up to 50% aromatic contents, in refineries, factories and vessels.
Tube	Oil resistant synthetic rubber
Reinforcement	High tensile synthetic fabric with steel helical embedded wire
Cover	Weather, ozone and oil resistant synthetic rubber
Marking	INTER OSD150 OIL SUCTION & DISCHARGE HOSE - BP 450PSI - WP 150PSI



Smooth



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1	25	25.4	36.4	10	150	30	450	BI-51101	BI-61101
1.1/4	32	32.0	43.0	10	150	30	450	BI-51102	BI-61102
1.1/2	38	38.0	50.0	10	150	30	450	BI-51103	BI-61103
2	51	50.8	62.8	10	150	30	450	BI-51104	BI-61104
2.1/2	63	63.5	78.3	10	150	30	450	BI-51105	BI-61105
3	76	76.2	91.0	10	150	30	450	BI-51106	BI-61106
3.1/2	90	88.9	103.7	10	150	30	450	BI-51107	BI-61107
4	102	101.6	117.6	10	150	30	450	BI-51108	BI-61108
5	127	127.0	147.8	10	150	30	450	BI-51109	BI-61109
6	152	152.4	175.2	10	150	30	450	BI-51110	BI-61110

For sizes other than listed above, please contact us

Flat-Corrugated



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1.1/4	32	32.0	42.8	10	150	30	450	BI-21002	BI-61102C
1.1/2	38	38.0	51.0	10	150	30	450	BI-21003	BI-61103C
2	51	50.8	62.6	10	150	30	450	BI-21004	BI-61104C
2.1/2	63	63.5	77.9	10	150	30	450	BI-21005	BI-61105C
3	76	76.2	90.6	10	150	30	450	BI-21006	BI-61106C
3.1/2	90	88.9	104.0	10	150	30	450	BI-21007	BI-61107C
4	102	101.6	120.0	10	150	30	450	BI-21008	BI-61108C
5	127	127.0	148.0	10	150	30	450	BI-21009	BI-61109C
6	152	152.4	175.2	10	150	30	450	BI-21010	BI-61110C

For sizes other than listed above, please contact us

Air Hose

Water Hose

Gas & Welding
Hose

Abrasion Material
Hose

Oil / Petroleum
Hose

Chemical
Hose

Automotive
Hose

OIL SUCTION & DISCHARGE HOSE 250PSI

Air Hose

Water Hose

Gas & Welding
Hose

Abrasion Material
Hose

Oil / Petroleum
Hose

Chemical
Hose

Automotive
Hose



Applications

For suction and discharge of petroleum products, of up to 50% aromatic contents, in refineries, factories and vessels.

Tube

Oil resistant synthetic rubber

Reinforcement


High tensile synthetic fabric with steel helical embedded wire

Cover

Weather, ozone and oil resistant synthetic rubber

Marking

INTER OSD250 OIL SUCTION & DISCHARGE HOSE - BP 750PSI - WP 250PSI



Smooth



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1	25	25.4	37.0	17	250	51	750	BI-51211	BI-61211
1.1/4	32	32.0	44.0	17	250	51	750	BI-51212	BI-61212
1.1/2	38	38.0	51.0	17	250	51	750	BI-51213	BI-61213
2	51	50.8	65.0	17	250	51	750	BI-51214	BI-61214
2.1/2	63	63.5	79.5	17	250	51	750	BI-51215	BI-61215
3	76	76.2	92.2	17	250	51	750	BI-51216	BI-61216
3.1/2	90	88.9	106.9	17	250	51	750	BI-51217	BI-61217
4	102	101.6	118.8	17	250	51	750	BI-51218	BI-61218
5	127	127.0	147.4	17	250	51	750	BI-51219	BI-61219
6	152	152.4	177.2	17	250	51	750	BI-51220	BI-61220

For sizes other than listed above, please contact us

Flat-Corrugated



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1	25	25.4	37.0	17	250	51	750	BI-51211C	BI-61211C
1.1/4	32	32.0	44.0	17	250	51	750	BI-51212C	BI-61212C
1.1/2	38	38.0	51.0	17	250	51	750	BI-51213C	BI-61213C
2	51	50.8	65.0	17	250	51	750	BI-51214C	BI-61214C
2.1/2	63	63.5	79.5	17	250	51	750	BI-51215C	BI-61215C
3	76	76.2	92.2	17	250	51	750	BI-51216C	BI-61216C
3.1/2	90	88.9	106.9	17	250	51	750	BI-51217C	BI-61217C
4	102	101.6	118.8	17	250	51	750	BI-51218C	BI-61218C
5	127	127.0	147.4	17	250	51	750	BI-51219C	BI-61219C
6	152	152.4	177.2	17	250	51	750	BI-51220C	BI-61220C

For sizes other than listed above, please contact us